

# UniVent 1350

## INSTALLATION MANUAL

TABLE OF CONTENTS.....

2

GENERAL CONSTRUCTION NOTES.....

3

VENT INFORMATION.....

4

PARTS LIST.....

5-7

VERIFY FRAME OPENING .....

8

WINDOW FRAME PREPARATION.....

9

INSTALLATION INTO WINDOW WALL 900RW.....

10

INSTALLATION INTO CURTAIN WALL.....

11

INSTALLATION INTO STOREFRONT .....

12

GLAZING.....

13-14


SCREEN INSTALLATION.....

15

HARDWARE ADJUSTMENTS.....

16

1. These instructions cover typical product application, fabrication, installation and standard conditions and are general in nature. They provide useful guidelines, but the final shop drawings may include additional details specific to the project. Any conflict or discrepancies must be clarified prior to execution.
2. Materials stored at the job site must be kept in a safe place protected from possible damage by other trades. Stack with adequate separation so materials will not rub together and store off the ground. Cardboard or paper wrapped materials must be kept dry. Check arriving materials for quantity and keep a record of where various materials are stored.
3. All field welding must be done in accordance with CSA guidelines. All aluminum and glass should be shielded from field welding to avoid damage from weld splatter. Results will be unsightly and may be structurally unsound. Advise general contractor and other trades accordingly.
4. Coordinate protection of installed work with general contractor and/or other trades.
5. Coordinate sequence of other trades which affect framing installation with the general contractor (e.g. fire proofing , back up walls, partitions, ceilings, mechanical ducts, HVAC, etc.).
6. General contractor should furnish and guarantee bench marks, off set lines and opening dimensions. These items should be checked for accuracy before proceeding with erection. Make certain that all adjacent substrate construction is in accordance with the contract documents and/or approved shop drawings. If not, notify the general contractor in writing before proceeding with installation because this could constitute acceptance of adjacent substrate construction by others.
7. Isolate all aluminum to be placed directly in contact with masonry or other incompatible materials with a heavy coat of zinc chromate or bituminous paint. Fasteners attaching framing to building structure are typically not provided by Tubelite, nor specified in these instructions due to varying perimeter conditions and job performance requirements. Consult approved shop drawings.
8. Sealant selection is the responsibility of the erector, installer and/or glazing contractor and must be approved by the sealant manufacturer with regard to application and compatibility for its intended use. All sealants must be used in strict accordance with the manufacturer's instructions and applied only by trained personnel to surfaces that have been properly prepared.
9. Sealant must be compatible with all materials with which they have contact, including other sealant surfaces. Consult the sealant manufacturer for recommendations relative to shelf life, compatibility, cleaning of substrate, priming, tooling adhesion, etc. Recommend sealant manufacturer perform adhesion "pull test" at "wet" glazing for quality assurance.
10. Drainage gutters and weep holes must be kept clean at all times. Tubelite will not accept responsibility for improper drainage as a result of clogged gutters and weep holes.
11. All framing members, entrances and other materials are to be installed plumb, level and true with regard to established bench marks, column center lines or other working points established by the general contractor and checked by the erector, installer and/or glazing contractor.
12. Cleaning of exposed aluminum surfaces should be done per FGIA recommendations.
13. Due to varying perimeter conditions and job performance requirements, anchor fasteners are not specified in these instructions. For anchor fastening, refer to the shop drawings or consult the fastener supplier.
14. Codes governing the design and use of products vary widely. Tubelite does not control the selection of products configurations, operating hardware, or glazing materials, and assumes no responsibility for these considerations. It is the responsibility of the owner, specifier, architect, general contractor and the installer to make these selections in strict conformance with all applicable codes.
15. Check weblink below for any installation instruction updates
16. [ ] Dimensions in brackets are in [mm] millimeters




### 1350 PO AWNING INFORMATION DUAL GLAZED

CAM HANDLES	
*MIN DIMENSIONS	16" x 16" [406 x 406]
*MAX DIMENSIONS	60" x 36" [1524 x 914]
SCREEN	OPTIONAL with WICKET
MAX OPENING	VARIES
LIMITED OPENING	OPTION @ 4" [102]
CUSTODIAL HANDLE	N/A

ROTO-MPL	
*MIN DIMENSIONS	21" x 18" [533 x 457]
*MAX DIMENSIONS	38" x 80" [965 x 2032] or 60" x 50" [1524 x 1270] or max. 21 ft <sup>2</sup> [ 1.95 m <sup>2</sup> ]
SCREEN	OPTIONAL
MAX OPENING	2 1/4" < 32" [57 < 813] 7 1/2" > 32" [191 > 813]
LIMITED OPENING	**OPTION @ 4" [102]
CUSTODIAL HANDLE	OPTIONAL

\*Based on (DLO) dimensions  
[ ] Dimensions in brackets are in [mm] millimeters




### 1350 PO CASEMENT INFORMATION DUAL GLAZED

CAM HANDLES	
*MIN DIMENSIONS	**16" x 16" [406 x 406]
*MAX DIMENSIONS	**35" x 54" [889 x 1372]
SCREEN	OPT. (wicket)
MAX OPENING	6"- 8" [152-203]
EGRESS	OPTIONAL
LIMITED OPENING	OPTION @ 4"
CUSTODIAL LOCK	N/A

ROTO-MPL	
*MIN DIMENSIONS	**16 5/8" x 21" [422 x 533]
*MAX DIMENSIONS	**35" x 62" [889 x 1575] or 27" x 80" [686 x 2032]
SCREEN	OPTIONAL
MAX OPENING	6"-8" [152-203]
EGRESS	OPTIONAL
LIMITED OPENING	OPTION @ 4" [102]
CUSTODIAL LOCK	OPTIONAL


Based on (DLO) dimensions  
\*\*Width/Height ratio exceeding 65% is not recommended  
[ ] Dimensions in brackets are in [mm] millimeters



### 1350 PI HOPPER INFORMATION DUAL GLAZED

	MPL	CAM HANDLES
*MIN DIMENSIONS	16" x 16" [406 x 406]	16" x 16" [406 x 406]
*MAX DIMENSIONS	60" x 36" [1524 x 914] or 36" x 54" [914 x 1372]	48" x 36" [1219 x 914]
SCREEN	STANDARD	STANDARD
MAX OPENING	VARIES	VARIES
EGRESS	NA	NA
LIMITED OPENING	STANDARD @ 4"	STANDARD @ 4"
CUSTODIAL HANDLE	STANDARD	N/A

\*Based on (DLO) dimensions  
[ ] Dimensions in brackets are in [mm] millimeters




### 1350 PI CASEMENT INFORMATION DUAL GLAZED


	MPL	CAM HANDLES
*MIN DIMENSIONS	**18" x 24" [457 x 607]	**18" x 24" [457 x 610]
*MAX DIMENSIONS	**35" x 80" [889 x 2032]	**32" x 54" [813 x 1372]
SCREEN	OPTIONAL	OPTIONAL
MAX OPENING	VARIES	VARIES
EGRESS	OPTIONAL	OPTIONAL
LIMITED OPENING	OPTIONAL @ 4"	OPTIONAL @ 4"
CUSTODIAL HANDLE	OPTIONAL	NA

\*Based on (DLO) dimensions  
\*\*Width/Height ratio exceeding 65% is not recommended  
[ ] Dimensions in brackets are in [mm] millimeters


## Multi Point Lock MPL (PO, Used with ROTO Operator)




LINEAR HANDLE		
PART #	FINISH	USED WITH
1162001	SILVER	1162304 Backer Plate
1162105	WHITE	1162203 Gasket
1162103	BLACK	7200201 Machine Screw





MPL LOCK BAR		
PART #	SIZE	USED WITH
1168001	12	116200x Linear Handle
1168101	24	PA133500x Custodial Lock
1168201	36	PA133600x ADA Extended
1168301	48	7238101 Machine Screw



MPL EXTENSION BAR		
PART #	SIZE	USED WITH
1163001	6	
1162901	10	1168x01 Lock Bar
1162801	14	7238101 Machine
1162701	18	Screw
1162601	22	



1162203 MPL GASKET

1162404 MPL KEEPER  
used with 72381017200201  
10-32 x  $\frac{3}{4}$  PHS, SS

1162304 MPL BACKER PLATE


7238101  
10-24 x  $\frac{3}{8}$  FHS, SS

## CAM Handle Locking Hardware (PO)



CAM HANDLE LH		
PART #	FINISH	USED WITH
1147101	WHITE BRONZE	1147301 Surface Strike 7238101 Machine Screw


CAM HANDLE RH		
PART #	FINISH	USED WITH
1147201	WHITE BRONZE	1147301 Surface Strike 7238101 Machine Screw



1147301 SURFACE STRIKE

7238101 10-24 x  $\frac{3}{8}$  FHS, SS

## Custodial Lock (OPTIONAL)




OPTIONAL


PO CUSTODIAL LOCK		
PART #	FINISH	USED WITH
PA1335001	SILVER	PA1337001 Handle
PA1335005	WHITE	1162203 Gasket
PA1335003	BLACK	7240101 Machine Screw

OPTIONAL  
SHIP LOOSEPA1337001  
REMOVABLE  
CUSTODIAL HANDLE


## Hinges (PO)



4-BAR HINGE, AWNING	
PART #	SIZE
1171001	10
1171601	16
1172401	24
1142701	28
Used with 7237301	







BUTT HINGE RH, CASEMENT	
PART #	FINISH
1452741	SILVER
1452773	BLACK
1452709	PAINTED
Used with 7237001	




BUTT HINGE LH, CASEMENT	
PART #	FINISH
1453741	SILVER
1453773	BLACK
1453709	PAINTED
Used with 7237001	

7237001 10 x  $\frac{1}{2}$  PHS, SS7237301 10 x  $\frac{3}{8}$  PHS, SS



## MISC.

1167003  
SNUBBER SET  
used with 72381011140501  
FRICTION  
ADJUSTOR/LIMITER  
used with 72370011476203  
EPDM SETTING BLOCK

OPTIONAL

1141603  
AWNING LIMIT BLOCK, 2  $\frac{1}{4}$   
used with 7234701

OPTIONAL


1142003  
CSMT LIMIT BLOCK, 3  
used with 72347011141501  
ADJUSTING SCREW PVC SHIM  
used on casement only7234701 10 x  $\frac{7}{8}$  PHS, SS7203901  
ADJUSTING SCREW  
used on casement only

OPTIONAL


PI EURO CUSTODIAL LOCK		
PART #	FINISH	USED WITH
PA4700901	SILVER	PA4701000
PA4700905	WHITE	Security Wrench
PA4700903	BLACK	

OPTIONAL  
SHIP LOOSEPA4701000 MAINTENANCE  
WRENCH  
used with PA470090X


## ROTO OPERATOR (PO)



9 1/2 ROTO RH, CASEMENT		
PART #	FINISH	USED WITH
1451501	SILVER	1450402 Gasket
1451503	BLACK	7200104 Socket H.Screw
1451505	WHITE	1452101 13 1/2 TRACK



9 1/2 ROTO LH, CASEMENT		
PART #	FINISH	USED WITH
1451601	SILVER	1450402 Gasket
1451603	BLACK	7200104 Socket H.Screw
1451605	WHITE	1452101 13 1/2 TRACK



27 3/4 ROTO, AWNING		
PART #	FINISH	USED WITH
1450001	SILVER	1150402 Gasket
1450003	BLACK	7280104 Socket H.Screw
1450005	WHITE	1149801 13 7/8 TRACK



7200104 10-24 x 1/2 SHS, SS





7280104 8-32 x 1/2 SHS, SS

13 1/2 ROTO RH, CASEMENT		
PART #	FINISH	USED WITH
1451701	SILVER	1450402 Gasket
1451703	BLACK	7200104 Socket H.Screw
1451705	WHITE	1452101 13 1/2 Track


13 1/2 ROTO LH, CASEMENT		
PART #	FINISH	USED WITH
1451801	SILVER	1450402 Gasket
1451803	BLACK	7200104 Socket H.Screw
1451805	WHITE	1452101 13 1/2 Track

16 3/4 ROTO, AWNING		
PART #	FINISH	USED WITH
1450501	SILVER	1150402 Gasket
1450503	BLACK	7280104 Socket H.Screw
1450505	WHITE	1450601 8 3/8 Track


OPTIONAL  
SHIP LOOSEOPTIONAL  
SHIP LOOSE

ROTO HANDLE		
PART #	FINISH	USED WITH
1449901	SILVER	ROTO OPERATORS
1449902	BRONZE*	
1449903	BLACK	
1449905	WHITE	


FOLDING ROTO HANDLE		
PART #	FINISH	USED WITH
1459901	SILVER	ROTO OPERATORS
1459902	BRONZE*	
1459903	BLACK	
1459905	WHITE	



1450601 8 3/8 TRACK, AWNING



1149801 13 7/8 TRACK, AWNING



1452101 13 1/2 TRACK, CASEMENT




1450401 GASKET, CSMT



1150402 GASKET, AWNING






## Multi Point Lock MPL (PI)




MULTIPOINT IN-SWING HANDLE		
PART #	FINISH	USED WITH
PA1338001	SILVER	1173801
PA1338005	WHITE	
PA1338003	BLACK	



1173801 HANDLE CONNECTION


1172603  
ADJUSTABLE IN-SWING KEEPER6220301  
SNUBBER IN-SWING1172703  
END LOCKING BOLT1173003  
INTERMEDIATE LOCKING BOLT1173701  
CORNER DRIVE1174501  
FRICTION LIMIT DEVICE

## Hinges (PI)




4-BAR HINGE, HOPPER		
PART #	SIZE	
1171001	10	
1171601	16	
1172401	24	
1142701	28	

Used with 7237001



1457100 CASEMENT HINGE



4-BAR HINGE SHIM		
PART #	SIZE	
1490503	10	
1490903	16	
1490603	24 & 28	

Used with 4-BAR HINGE



7237001 10 x 1/2 PHS, SS



## IN-SWING CAM HANDLE



IN-SWING RING CAM HANDLE (LH)		
PART #	FINISH	USED WITH
1449101	SILVER	1448802 Gasket 7238101 Screw
1449103	BLACK	
1449105	WHITE	



IN-SWING RING CAM HANDLE (RH)		
PART #	FINISH	USED WITH
1449201	SILVER	1448802 Gasket 7238101 Screw
1449203	BLACK	
1449205	WHITE	

1448802  
GASKET1448901  
KEEPER SHIM1449001  
UNIVERSAL KEEPER  
*used with 7237001*1148001  
RING PULL SPRING CATCH  
*used with 7238101*


OPTIONAL

1147803  
GASKET FOR SPRING CATH7238101  
10-24 x 3/8 FHS, SS7237001  
10 x 1/2 PHS, SS


## Insect Screen Components



SHIP LOOSE

1159101  
1/2 SCREEN TURN CLIP  
*(used on PO with ROTO hardware)*

SHIP LOOSE

7248101  
#8 x 3/8 PHS, SS













SHIP LOOSE

1159301  
1" SCREEN TURN CLIP  
*(used on PI and PO with wickets)*

SHIP LOOSE


7243101  
#8 x 1 3/8 PHS, SS

Extrusions


 1466001 PVC POCKET FILLER FOR SHIM TAPE	 2250803 PolyShim Tape 3/16"x 25'	 1841003 GLAZING GASKET, 1" [25] GLASS SHIP LOOSE	 5100701 WEATHERSTRIPPING PILE	 1461003 CENTRAL SEAL GASKET, PI	 1462003 PERIMETER BULB GASKET
 EA135005 PO GLASS STOP	 EA135011 PI GLASS STOP	 1474003 PI CW ADAPTOR-DUAL GLAZED PVC	 1350103 FB FLUSHGLAZE PVC ADAPTOR SHIP LOOSE		
 SHIP LOOSE ORDERED SEPR. TA9404 POCKET FILLER WITH LEG FOR FLAT BACK INSTALLATION	 SHIP LOOSE ORDERED SEPR. P4563 JAMB POCKET FILLER FOR SF INSTALLATION				

## STEP 1

- Make sure vent opening is plumb and level. Measuring corner-to-corner is easiest way to make sure it is square. See **FIG. 1**
- Make sure frame size is smaller than Window Opening. See **FIG. 2**
- See **FIG. 2** to measure and verify GLASS SIZE.




**FIG. 1**



**1350 PO**  
FLAT BACK INSTALLATION

**FRAME SIZE**  
=DLO - 1/4"


**GLASS SIZE**  
Width = DLO - 4 9/16  
Height = DLO - 4 5/8



**1350 PO**  
CURTAIN WALL INSTALLATION

**FRAME SIZE**  
=DLO - 1/4"


**GLASS SIZE**  
=DLO - 4 3/8



**1350 PO**  
STOREFRONT INSTALLATION

**FRAME SIZE**  
=DLO - 1/4"


**GLASS SIZE**  
Width = DLO - 4 9/16  
Height = DLO - 4 5/8



**1350 PI**  
FLAT BACK INSTALLATION

**FRAME SIZE**  
=DLO - 1/4"


**GLASS SIZE**  
=DLO - 5.00



**1350 PI**  
CURTAIN WALL INSTALLATION

**FRAME SIZE**  
=DLO - 1/4"

**GLASS SIZE**  
=DLO - 5 5/8



**1350 PI**  
STOREFRONT INSTALLATION

**FRAME SIZE**  
=DLO - 1/4"

**GLASS SIZE**  
=DLO - 5.00

**FIG. 2**

## SYSTEM COMPATIBILITY

**WINDOW WALL:**  
900RW T<sup>\*1</sup>  
900RW TU<sup>\*1</sup>

**CURTAINWALL:**  
200<sup>\*2</sup>, 400CW<sup>\*2</sup>, 400SS<sup>\*2</sup>,  
400T<sup>\*2</sup>, 400TU<sup>\*2</sup>

**STOREFRONT:**  
E1400<sup>\*3</sup>, T14000,  
E14000 I/O<sup>\*3</sup>, T14000 I/O, TU24000  
E24650<sup>\*1\*3</sup>, T24650<sup>\*1</sup>

<sup>\*1</sup> not compatible with SSG condition


<sup>\*2</sup> installed from exterior only

<sup>\*3</sup> Please note, in this application the vents can be installed but will thermally bridge.




## STEP 1

- Drill Ø.201 [5] clearance holes for #10 Screws using #7 Drill bit for anchoring holes, as per recommended location, see **FIG. 1**.
- See **FIG. 2** for recommended spacing of clearance holes. Double check anchor size and location as per shop drawings.



**FIG. 1**



△ RECOMMENDED ANCHORING LOCATION

**FIG. 2**

**A=5" [127]**

**B= max 18" O.C [457]**

**C= if Frame Width >36" [914]**

STEP 1

- a. Pre-drill and countersink TA9404 pocket filler for #10 FHS, 2" from each end and 16" O.C. using V-groove as reference. **See FIG. 1**
- b. Install continuous TA9404 Pocket Filler at both jambs and head using S444 fastener (#10 x 1/2" FHS Self Drilling. **See FIG. 2**
- c. Install 2 1/2" long TA9404 at sill from both sides tight against adjacent pocket filler. Fasten using one S444 screw in the center of the V-groove. Seal fasteners with sealant. **See FIG. 3**
- d. Add additional 2 1/2" long TA9404 at the sill if the frame opening width is larger then 36".




FIG. 1



REFER TO FRAMING SYSTEMS  
FAB/INSTALLATION MANUAL FOR  
COMPLETE FABRICATION INSTRUCTIONS

**NOTE:** IPA 2 method- dispense Iso-Propanol Alcohol (IPA) on a cloth, gently wipe the area. Immediately use another lint-free clean cloth to wipe the area dry.




FIG. 2




FIG. 3




FIG. 4

STEP 2

- a. Set Horseshoe shims onto the sill opening at each corner. Carefully set the vent onto the shims . **See FIG. 4 & FIG. 5**
- b. Position window frame in the opening, use **FIG. 7** as guide.
- c. Ensure weep holes are not blocked. Refer to **FIG. 3**
- d. Once vent is positioned, carefully open the sash and place a temporary fastener near the top hinge through the clearance hole.
- e. Place appropriate horseshoe shims around the perimeter, ensure window is square and plumb. Fasten in all remaining areas. Use #10 x 1 1/2" SELF DRILLING Screw.
- f. Check corners of the frame/sash at the lock side to make sure they are aligned on the lock side, adjust shims if necessary. **See FIG. 6**
- g. Seal all the screw heads.




FIG. 5




FIG. 6




FIG. 7

SEE GLAZING

- a. Refer to GLAZING INSTRUCTIONS before proceeding to STEP 3.

STEP 3

- a. Check operation of the window by opening and closing multiple times.
- b. Cut horseshoe shims flush to interior/exterior frame surface.
- c. Clean perimeter of the frame where seal will be applied using IPA 2 METHOD.
- d. Apply Interior/Exterior seal around the frame and tool.

DEPTH REFERENCE		
VENT TYPE	RECEIVING SYSTEM	
	900RW (4 1/2")	900RW (6")
1350 PO	1 5/8"	3 1/8"
1350 PI	2.00"	3 1/2"

## STEP 1


- Clean the around the corners of the frame using IPA2 METHOD.
- Apply a bed of sealant 2" [51] around each corner of the frame ensuring it comes in contact with the gasket. Apply a dab of sealant on the the gasket joints. See **FIG. 1**

**NOTE:** IPA 2 method-dispense Iso-Propanol Alcohol (IPA) on a cloth, gently wipe the area. Immediately use another lint-free clean cloth to wipe the area dry.




REFER TO FRAMING SYSTEMS  
FAB/INSTALLATION MANUAL  
FOR COMPLETE FABRICATION  
INSTRUCTIONS

**FIG. 1**




## STEP 2

- Clean exterior area of the vent where it will come in contact with the primary gasket using IPA 2 method
- Set Horseshoe shims onto the sill opening at each corner. Carefully set the vent onto the shims. See **FIG. 2**
- Push the vent in tight to the primary gasket seal. See **FIG. 3**
- Place temporary shims 1/4" [6] between sash and frame maintaining consistent gap. This will prevent bowing and shifting of the vent during pressure plate installation. See **FIG. 4**
- Install exterior pressure plates ensuring drainage slots are facing up. **FIG. 5**, ensure window remains square.
- For windows exceeding 36" [914] in height or width, place an anchoring screw. Refer to **FIG. 4 on Page 6**
- For casements windows, an additional fastener is needed beside the top hinge. Refer to **FIG. 4 on Page 8**
- Check sight line, adjust if necessary. See **FIG. 6**



**FIG. 2**



## SEE GLAZING



**FIG. 3**

**FIG. 4**

**FIG. 5**




**FIG. 6**

## STEP 3


- Check operation of the window by opening and closing multiple times.
- Cut horseshoe shims flush to interior/exterior frame surface.
- Clean perimeter of the frame where seal will be applied using IPA 2 METHOD.
- Apply Interior/Exterior seal around the frame and tool.
- Seal all the screw heads.

## STEP 1


- Install **P4563 Pocket Filler** at jambs at each side. See **FIG. 1**
- Install 1350103 PVC adaptor at sill & head only. See **FIG. 2**
- Insert and slide top of the window into the glazing pocket. See **FIG. 3**
- Swing bottom of the window into place **FIG 4**. Set plastic horseshoe shims on the sill at each corner. See **FIG. 6**
- Snap glass stop into place. See **FIG. 5**




**FIG. 1**




**FIG. 2**




**FIG. 3**



**FIG. 4**




**FIG. 5**



**FIG. 6**

## STEP 2

- Place appropriate horseshoe shims around the perimeter, ensure window is square and plumb. Fasten the jambs of the frame **FIG 7**, refer to **FIG. 4 on Page 8** for spacing schedule .




**FIG. 7**

## SEE GLAZING

- Refer to GLAZING INSTRUCTIONS before to proceeding to STEP 3.

## STEP 3

- Check operation of the window by opening and closing multiple times.
- Cut horseshoe shims flush to interior/exterior frame surface.
- Clean perimeter of the frame where seal will be applied using IPA 2 METHOD.
- Apply Interior/Exterior seal around the frame and tool. See **FIG. 8**
- Seal all the screw heads.



**FIG. 8**

## STEP 1

- Carefully remove glass stops around the interior perimeter of the sash.
- Clean the exterior glazing leg by using IPA 2 wipe method. Apply 1/8" PolySHIM tape ensuring it is not loose or wavy. Ensure that the corners of the tape do not overlap. See **FIG. 1**
- Peel back the adhesive backing from the glazing tape.
- Apply a bed of sealant 2" [51] around each corner of the sash ensuring it comes in contact with glazing tape. Apply a light bead of sealant to the glazing tape joint.




FIG. 1




FIG. 2







FIG. 3

## STEP 2


- Inspect glass unit for any sealant overlap, clean as necessary. Using IPA2 method clean 2" [51] of interior/exterior glass surface all around the perimeter.
- Place setting blocks at each corner, approximately 4"-6" [102-152] from the corner. Dab of sealant can be used to hold it in place. See **FIG. 4**
- Carefully slide the glass into glazing pocket at the top, set the glass onto the Setting Blocks and center the glass into the sash opening. See **FIG. 5**
- Ensure sight lines are even on all sides, sash must be square.
- Place PVC shim used for Adjusting Screw for Casement Out-swing only. Adjust screw to be snug. See **FIG. 4** (comes pre-installed)




Hopper PI



Casement PI



Awning PO



Casement PO

FIG. 4





FIG. 5


NEXT PAGE

**STEP 3**

- a. Using a mallet hammer install glass stops, starting with horizontals. See **FIG. 1**
- b. Repeat same step for vertical glass stops.

**FIG. 1****STEP 4**

- c. Insert glazing gasket starting from one end, repeat this every 16" [406]. Ensure opposite end of the gasket is inserted before rolling remaining gasket. See **FIG. 2**
- d.

**FIG. 2**



STEP 1

- a. Install supplied screen clips & fasteners on all the pre-drilled pilot holes. See **FIG. 1**
- b. Ensure screen clip is snug and free to rotate.
- c. Insert supplied screen frame in between the screen clips. See **FIG. 2**
- d. Rotate screen clips to lock the screen frame in place. See **FIG. 3**

SCREEN CLIP SCHEDULE		
Screen HEIGHT	Screen WIDTH	
	W<48"	W>48"
H<48"	4x	6x
H>48"	6x	8x





FIG. 2




FIG. 3

**Insect Screen Components**

SHIP LOOSE

**1159101**  
**5/16" SCREEN TURN CLIP**  
(used on PO with ROTO hardware)

SHIP LOOSE

**7248101**  
**#8 x 5/8" PHS, SS**

SHIP LOOSE


**1159301**  
**1" SCREEN TURN CLIP**  
(used on PI and PO with wickets)

SHIP LOOSE

**7243101**  
**#8 x 1 3/8" PHS, SS**

## LIMIT BLOCK REMOVAL/REINSTALL

- Open sash using ROTO operator.
- Locate LIMIT BLOCK next to ROTO arms
- Remove fastener by using #2 SQUARE DRIVE
- Prior to reinstalling LIMIT BLOCK apply sealant into fastener hole
- Place LIMIT BLOCK back into its place, fasten using #2 SQUARE DRIVE. See **FIG. 1**




**FIG. 1**

**FIG. 2**

## FRICION ARM LIMIT DEVICE REMOVAL/REINSTALL


- Vents equipped with FRICTION ARM LIMIT DEVICE can be removed to aid with anchor screw installation.
- Open sash to the maximum, locate LIMIT DEVICE inside of the Friction Arm, if applicable. See **FIG. 2**
- Remove 2 #10 fasteners holding LIMIT DEVICE.
- Temporarily place same fasteners back into the Friction Arm securing the hinges.
- If larger opening is desired trim LIMIT DEVICE as needed. See **FIG. 3**. Once installation and any adjustments are complete, bring sash to the original opening and install LIMIT DEVICE into its place.




**FIG. 3**

## CASEMENT FRICTION ADJUSTOR/LIMITER

- Open sash, locate Friction Adjustor bracket located on the frame.
- Remove 2 fasteners holding the bracket on the frame side. See **FIG. 4**
- Sash can be opened to the full extend for any maintenance or installation work.
- Over time friction must be adjusted, this can be done by using 3/32 HEX KEY, adjusting screw is located on top of sliding shoe within the track. See **FIG. 5**
- Reinstall the bracket to its place using original fasteners.




**FIG. 5**



**FIG. 4**

## PI CASEMENT HINGE ADJUSTMENT (EGRESS)


- Open sash, remove FRICTION ADJUSTOR if applicable
- Locate adjusting screws at the bottom and the top hinge.
- Using 4mm HEX KEY adjust hinge if needed as per **FIG. 6**
- Reinstall FRICTION ADJUSTOR.
- Close sash and check for any interferences.



**FIG. 6**

## MPL COMPRESSION ADJUSTMENTS

- To adjust compression open the sash and locate MPL lock points.
- Using 3/16 HEX KEY adjust cam bolts. **FIG. 7**
- Lock the handle, sash must compress up to 1/8" [3] from the initial surface contact with the bulb seal.



**FIG. 7**

Project-Out

Project-In